

电机编码器连接器定义
编码器型号：
SRMA46-17Bit-SYBS-C-5V
(17位单圈磁编)

MT60及SH3.5插头




电机动力连接器定义

A 3D perspective diagram of a 10-pin connector. The connector has a rectangular body with a top flange. Four pins are labeled: PIN1 (top left), PIN3 (top right), PIN7 (bottom left), and PIN10 (bottom right). The pins are arranged in two rows of five.

端子号	信号
1	5V
2	0V
3	SD+
4	SD-
5	
6	
7	
8	
9	屏蔽



端子 记号	信号
1	U
2	V
3	W
金插 SH3.5	PE

						<div><div><div><div><div></div><div>VMORE</div></div><div><div>SERVO MOTOR</div><div>VMJM08075B30CGN510</div></div><div><div><div>48VDC</div><div>19Amps</div><div>750W</div></div><div><div>2.39Nm</div><div>3000/min</div><div>1m F</div></div></div><div><div>VMORE CTRL TECH CO.,LTD.</div><div>IP65</div></div><div><div>SERIAL: 60008881</div><div></div><div></div></div></div></div></div>	深圳市微秒控制技术有限公司			
标记	处数	分区	更改文件号	签名	年、月、日			规格书		
设计			标准化				阶段标记	重量	比例	
									1:2	
审核								VMJM08075B30CGN51		
工艺			批准			共	张	第	张	60008881